

TeleControl Serie 21 , 4 Botones , 2 Velocidades, Alcance 100Mts



Especificaciones Técnicas

Channels	4	Control Speed	2 Speed
Transmitter Emergency Stop	Yes	Codigo FCC	OFNF21
Fuente de Alimentación del Transmisor	2 AA batteries	Distancia de Control	300 ft up to 600 ft with optional antenna
Código de Seguridad	32 bits (4.3 billion)	Potencia del Transmisor	≤10dBm
Rango de Frecuencia	VHF: 310~331 MHz; UHF: 425 ~ 446 MHz	Rango de temperatura de Trabajo	-40 ~ 185 °F / -40 ~ 85°C
Normas	FCC and OSHA standard 1910.179	Garantía	1 Year

F21-4S/4D TRANSMITTER

Economical, safe, convenient



MODEL: F21-4S-TX
ITEM CODE: 921-004-001
Dimensions: 156 x 61 x 51 mm
Weight: 255g (without batteries)

- Product Features:**
- 4 buttons (D means double steps), spare button
 - 8 control contacts.
 - With battery voltage warning device, the power supply is cut off during low power.
 - Program the button function by computer interface.
 - Up/Down, East/West can be programmed to interlock or non-interlock.
 - The spare button can be programmed to start, toggle or normal, etc.


- Standard Configuration:**
- One transmitter (with hanging belt)
 - One dust bag
 - One receiver
 - Receiver with 1.6 meter cable
 - Battery: One pair
 - One receiver antenna.
 - Operation and maintenance manual.

Safety features:
 Each radio remote control system functions in all manner of operational conditions equipped with their own unique identity code (ID-Code). This means that only the correct control unit can activate and control its matching receiver (crane/machine) for maximum safety. The system is FCC and CE certificates.

Transmitter Parameters: F21-TX	
Material	Glass-Fiber PA
Enclosure protection class	IP65
Frequency range	VHF: 310~331MHz; UHF: 425~446MHz
Transmitter power	< 10dBm
Transmitter power supply	2 AA batteries
Safety code	32 bits (4.3 billion)
Temperature range	-40° C → 85° C
Control distance	Approx 100m (200 meters is customized)



Start protection circuit
 Each system has a dedicated testing circuit. Before the system starts, the transmitting system tests all switch contacts and receiving system tests relays. Only if both procedures are passed the whole system starts working.



MODEL: F21-RXC
ITEM CODE: 921-100-112
Dimensions: 205 x 86 x 80 mm
Weight: 620 g



Transmitter Parameters: F21-XRC	
Material	Glass-Fiber PA
Enclosure protection class	IP65
Frequency range	VHF: 310~331MHz; UHF: 425~446MHz
Receiver sensitivity	< -110dBm
Receiver power supply	18~65V AC/DC, 65~440V AC/DC (optional)
Output contactor capacity	8A sealed relay output (with AC 250V/10A relays, 10A fuse)
Control distance	Approx 100m (200 meters is customized)
Safety code	32 bits (4.3 billion)
Temperature range	-40° C → 85° C



Connect buckle



Damping rubber



Safety Code

Application:
 Single-hook, single-speed electric hoist or hoist-type traffic and industrial remote control with 8 contacts or less.

Peso & Dimensiones

Peso Total

4 lbs / 2 Kg

Referential Images / Imágenes Referenciales

Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso