



GAS-POWERED PULLING WINCH. MAX. PULLING FORCE: 1000 KG Centrifugal Clutch - Including Accessories

Especificaciones Técnicas

Tambor Gira con motor en ralentí	No	Reductor	Aluminium alloy. Heat treated 3-stage helical & spur gears. Mounted on ball bearings. Oil bath lubrication.
Sistema de Retención de Cuerda	Quick release automatic anti roll-back mechanism (ARM)	Capacidad de Carga	Pulling Single Line: 2200 lb / 1000 kg Pulling Double Line: 4400 lb / 2000 kg Not for Lifting - No apto para Izaje
Velocidad /min	44 ft/min 13.4 m/min	Numero de Velocidades	1 Speed
Marca y modelo del motor	Honda GX50	Tipo de Motor	4-stroke - 360° inclinable - air-cooled 50 cc
Potencia Motor	1.47 kW 2.0 HP	RPM Motor	7000 rpm
Tipo Transmisión / Reductor	Centrifugal	Relación de Transmisión	200:1
Freno al Reductor	Anti-reversing roller clutch bearing	Cable Recomendado	Fiber Ø 3/8" (10 mm)
Tipo de Tambor	Capstan Cabrestante	Normas	CE
Fabricado en	Canada	Garantía	1 Year
BD ø Diámetro Tambor	Standard: Ø 3" (76 mm) 44ft/min 13.4 m/min Single line No optional drum		

Detalles del Empaque

A Altura Total	12
D Depth	12.01
W Ancho	17.01

Referential Images / Imágenes Referenciales
Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso