




Carro Electrico 3 Fases 5 Toneladas. Botonera No Incluida

Especificaciones Técnicas

Capacidad de Carga	11000 lb / 5000 kg	Voltaje	3 Phase 208~240/440~480V 50/60Hz
Velocidad del Trolley /min	43 ft / 13 m @ 60 HZ 36 ft / 11 @ 50 HZ	Rango de ancho de la Viga	4~7 in / 100~178 mm
Radio Minimo de Giro	5 ft / 1.5 m	Normas	ASME B30.17
Garantía	3 Year	T Motor del Carro	9.09 in / 231 mm
R Carro Ancho Caja	6 in / 142 mm		



Model / Modelo		PWQE1Ti	PWQE2Ti	PWQE3Ti	PWQE5Ti	PWQE7Ti	PWQE10Ti
Dimensions / Dimensiones	W	12.4 in / 315mm	12.7 / 325mm	13.3in / 340mm	15.7 in/ 400mm	26.5 in / 670 mm	19.6in / 500mm
	U	8.3 in / 212mm	8.6mm / 220mm	9.8 in / 250mm	11.4 in / 291mm	-	14.6in / 371mm
	R	5.5 in / 142mm	5.5 in / 142mm	5.5 in / 142mm	5.5 in / 142mm	9 in / 231 mm	5.5 in / 142mm
	T	9 in / 231mm	9 in / 231mm	9 in / 231mm	9 in / 231mm	5.6 in / 142 mm	9 in / 231mm

Peso & Dimensiones

Detalles del Empaque

Peso Total	180.4 lbs / 82 Kg	A Altura Total	11.5 in / 291 mm
		W Ancho	16 in / 400 mm

Referential Images / Imágenes Referenciales
Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso