



**1 ton Electric Chain Hoist w/ Power
Trolley 1 Speed 110V 1Ø, 60HZ 20ft
G100 Nickel Duty H2/M3**

Especificaciones Técnicas

Capacidad de Carga	1 ton	Numero de Velocidades	Variable Speed
Numero de Velocidades	1 Speed	Voltaje	1 Phase 120V 60Hz
Protección IEC Motor	IP55	Tipo Transmisión / Reductor	Spur gearbox
Tipo de Cadena	G100 Nickel	Dimensiones de la Cadena	7.1 mm
Caidas de Cadena	2	Longitud de cadena	40
Humedad	20%~90%	Temperatura	-4 ~ 104° F / -20 ~ 40° C
Potencia del Trolley	500	Cantidad de Velocidades	1
Normas	ASME HST-1 , ASME B30.16 , B30.17 , EN60204-35	Garantía	3 Year
Hoist Contactors Amps	25A	Hoist Contactor Coil Voltage	24 V
IEC Hoist IP Protection	IP55	Pendant Control Yes No	Yes
IEC Pendant Control Protection	IP66	Pendant Control Emergency Stop	Yes
Pendant Control total Length	17 ft	Hoist Motor Power in KW	0,75
Hoist Motor Insulation Grade	F	Optional Load Chain Brand & Country of Origin	FEC Japan or RUD Germany
Reducer Lubrication Type	Oil	Paint Specifications	Electrostatic Sprayed Plastic (ESP) Epoxy resins, Polyester Resins, Barium, Pigments
Standards Certified	CE	Trolley Motor Insulation Grade	F
Trolley Contactors Coil Voltage	24 V	Trolley Limit Switches	Yes
Trolley Wheel Diameter	95	Trolley Wheel Material	No. 45 steel
Trolley Minimum Turn Radius	1,3	Trolley Beam Range	2" to 6"
Trolley Beam Extension Kit	up to 12"	Load Chain weight per foot [lbs]	0.73
1st Package Type	Wood Crate	2nd Package Type	Wood Crate

Peso & Dimensiones

Peso Total	308 lbs / 140 Kg
-------------------	------------------

Detalles del Empaque

H Altura Muerta	25.39
------------------------	-------

A Altura Total	22.05
-----------------------	-------

D Depth	27.36
----------------	-------

W Ancho	16.54
----------------	-------

J Boca Gancho	2.32
----------------------	------

Peso Total (sin cable o cadena)	175.43
--	--------

Referential Images / Imágenes Referenciales
Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso