



330 Kg Mini Pro Electric Winch 12 mt. Milwaukee M18 x 2 Battery Powered Double Brake H3 Duty 16000 FLC

Especificaciones Técnicas

Capacidad de Carga	330 Kg	Battery	Not Included
EU File	Directive 2006/42/EC Machinery	Motor w/ foam shap	470uf/63V*2
Full Load Duty Cycles	16000	Power Battery Model	2 x Milwaukee M18 (Not Included)
Power Battery Voltage	18V x 2 Tot. 36V	Power Battery Location	Pendant Control
Pendant Control w/Quick Connector	Yes	Altura de Izaje Estandar (Customizable)	40 ft / 12 m
Velocidad /min	single line 6 m/min, doubl line 3 m/min	Numero de Velocidades	1 Speed
Voltaje	Milwaukee 18V x 2 = 36V	Clase de Servicio	A2 ED 40% / H3 / M4
Tipo de Motor	Brushless motor	Potencia Motor	850
AMP Motor	23	RPM Motor	12500
Freno Motor	Yes	Grado de Aislacion	B
Control	Pendant Control w/ E. Stop	Freno al Reductor	Yes
Tipo de Cadena	N/A	Normas	ASME/ANSI B30.7
Garantía	3 Year	IEC Pendant Control Protection	IP23
Pendant Control total Length	1.5 mt	Wireless Control Yes No	PWYT-W-SET-2C-BM
Wireless Control IP Protection	IP65	Standards Certified	CE / EMC EN ISO 12100, EN 14492-2, EN 60204-32, 2006/42/EC

Peso & Dimensiones

Peso Total	35.6 lbs / 17 Kg
-------------------	------------------

Detalles del Empaque

H Altura Muerta	22.4
------------------------	------

A Altura Total	25.2
-----------------------	------

D Depth	7.5
----------------	-----

W Ancho	14.6
----------------	------

J Boca Gancho	1.3
----------------------	-----

Peso Total (sin cable o cadena)	29.5 / 26.8
--	-------------

Referential Images / Imágenes Referenciales
Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso